

D-Bar(0°) Special angle specifications list

December , 2018

Spec	Right angle pitch	Reference depth	Reference cell volume
	(P mm)	(H μm)	(cm ³ /m ²)
P0.1H7S	0.1	7	4
P0.1H11K	0.1	11	6
P0.2H8K	0.2	8	6
P0.1H11K	0.1	11	7
P0.125H12K	0.125	12	8
P0.125H14K	0.125	14	8
P0.1H15K	0.1	15	8
P0.1H18S	0.1	18	9
P0.125H19K	0.125	19	11
P0.15H21S	0.15	21	13
P0.2H18K	0.2	18	13
P0.2H20K	0.2	20	13
P0.2H22K	0.2	22	15
P0.2H29K	0.2	29	18
P0.2H32K	0.2	32	18
P0.2H34K	0.2	34	19
P0.2H43K	0.2	43	22
P0.2H42K	0.2	42	23
P0.3H39K	0.3	39	25
P0.3H41K	0.3	41	26
P0.3H47K	0.3	47	28
P0.3H47K	0.3	47	30
P0.3H44K	0.3	44	30
P0.3H54K	0.3	54	33
P0.4H50K	0.4	50	37
P0.4H66K	0.4	66	48
P0.4H91K	0.4	91	58
P0.4H127K	0.4	127	68
P0.45H133K	0.45	133	77
P0.45H136K	0.45	136	91
P0.45H139K	0.45	139	91
P0.6H163K	0.6	163	103

•A difference in film thickness may occur depending on the coating conditions and the physical properties of the coating liquid.

•Some specifications are not listed. Please contact us if you do not have the required specifications.

•The reference depth and reference cell volume are possibility to change.

•Please contact us about specifications* because it may not be possible to manufacture depending on the size (diameter, length).



OSG SYSTEM PRODUCTS CO.,LTD.

TEL:0533-92-1511 FAX:0533-92-1512

E-mail:osp-info@osg.co.jp <http://www.j-osp.com/>