

特殊角度仕様一覧

φ40～φ62用

φ30以下用

φ30以下用(15°、30°、60°、85°)

φ30以下用(0°)

2018年12月

| 角度 | 呼び (線=L) | 歯直角ピッチ (P mm) | 参考深度 (H μm) | 参考セル容積 (cm ³ /m ²) |
|------|-------------|------------------|----------------|--|
| 45° | L20 | 1.2700 | 352 | 171 |
| | L25 | 1.0160 | 348 | 165 |
| | L30 | 0.8467 | 299 | 149 |
| | L36 | 0.7056 | 257 | 114 |
| | L40 | 0.6350 | 240 | 114 |
| | L45 | 0.5644 | 204 | 96 |
| | L50 | 0.5080 | 182 | 85 |
| | L55 | 0.4618 | 161 | 78 |
| | L60 | 0.4233 | 145 | 71 |
| | L65 | 0.3908 | 126 | 83 |
| | L70 | 0.3629 | 125 | 56 |
| | L75 | 0.3387 | 115 | 56 |
| | L80 | 0.3175 | 107 | 50 |
| | L85 | 0.2988 | 104 | 45 |
| | L90 | 0.2822 | 95 | 49 |
| | L95 | 0.2674 | 84 | 41 |
| | L100 | 0.2540 | 70 | 35 |
| | L105 | 0.2419 | | |
| | L110 | 0.2309 | 65 | 33 |
| | L120 | 0.2117 | 58 | 29 |
| | L130 | 0.1954 | 54 | 26 |
| | L140 | 0.1814 | 44 | 22 |
| | L150 | 0.1693 | 41 | 17 |
| | L160 | 0.1588 | | |
| L170 | 0.1494 | | | |
| L180 | 0.1411 | 35 | 17 | |
| L190 | 0.1337 | | | |
| L200 | 0.1270 | 26 | 14 | |
| L210 | 0.1210 | | | |
| L220 | 0.1155 | | | |
| L230 | 0.1104 | 28 | 14 | |
| L240 | 0.1058 | | | |
| L250 | 0.1016 | 28 | 13 | |
| L300 | 0.0847 | 22 | 11 | |
| L350 | 0.0726 | 12 | 6 | |
| L400 | 0.0635 | 6 | 3 | |

| 角度 | 呼び (線=L) | 歯直角ピッチ (P mm) | 参考深度 (H μm) | 参考セル容積 (cm ³ /m ²) |
|------|-------------|------------------|----------------|--|
| 45° | L20 | 1.2700 | 361 | 173 |
| | L25 | 1.0160 | | |
| | L30 | 0.8467 | | |
| | L36 | 0.7056 | 266 | 137 |
| | L40 | 0.6350 | | |
| | L45 | 0.5644 | 210 | 102 |
| | L50 | 0.5080 | 184 | 87 |
| | L55 | 0.4618 | | |
| | L60 | 0.4233 | 143 | 77 |
| | L65 | 0.3908 | | |
| | L70 | 0.3629 | 127 | 57 |
| | L75 | 0.3387 | | |
| | L80 | 0.3175 | | |
| | L85 | 0.2988 | 100 | 49 |
| | L90 | 0.2822 | 92 | 48 |
| | L95 | 0.2674 | | |
| | L100 | 0.2540 | 72 | 35 |
| | L105 | 0.2419 | | |
| | L110 | 0.2309 | 62 | 28 |
| | L120 | 0.2117 | | |
| | L130 | 0.1954 | 48 | 23 |
| | L140 | 0.1814 | | |
| | L150 | 0.1693 | 37 | 19 |
| | L160 | 0.1588 | | |
| L170 | 0.1494 | | | |
| L180 | 0.1411 | 35 | 16 | |
| L190 | 0.1337 | | | |
| L200 | 0.1270 | 31 | 17 | |
| L210 | 0.1210 | | | |
| L220 | 0.1155 | | | |
| L230 | 0.1104 | | | |
| L240 | 0.1058 | | | |
| L250 | 0.1016 | 25 | 14 | |
| L300 | 0.0847 | 23 | 11 | |
| L350 | 0.0726 | 16 | 8 | |
| L400 | 0.0635 | 11 | 7 | |

| 角度 | 呼び (溝仕様) | 歯直角ピッチ (P mm) | 参考深度 (H μm) | 参考セル容積 (cm ³ /m ²) | |
|-----------|-------------|------------------|----------------|--|---|
| 15° | P0.08H6S | 0.08 | 6 | 4 | |
| | P0.1H12S | 0.1 | 12 | 6 | |
| | ※WP0.3H15S | 0.3 | 15 | 8 | |
| | P0.1H16S | 0.1 | 16 | 9 | |
| | P0.2H28S | 0.2 | 28 | 10 | |
| | P0.2H24S | 0.2 | 24 | 11 | |
| | ※P0.2H33S | 0.2 | 33 | 18 | |
| | P0.25H40S | 0.25 | 40 | 20 | |
| | P0.25H54S | 0.25 | 54 | 26 | |
| | P0.3H62S | 0.3 | 62 | 32 | |
| | P0.4H71S | 0.4 | 71 | 37 | |
| | P0.4H82S | 0.4 | 82 | 41 | |
| | P0.508H197S | 0.508 | 197 | 98 | |
| | 30° | ※P0.2H15S | 0.2 | 15 | 8 |
| | | ※P0.2H15S | 0.2 | 15 | 9 |
| ※P0.3H17S | | 0.3 | 17 | 10 | |
| P0.2H20S | | 0.2 | 20 | 10 | |
| P0.25H40S | | 0.25 | 40 | 21 | |
| P0.25H56S | | 0.25 | 56 | 27 | |
| P0.3H62S | | 0.3 | 62 | 33 | |
| P0.4H79S | | 0.4 | 79 | 36 | |
| P0.4H72S | | 0.4 | 72 | 38 | |
| P0.2H81S | | 0.2 | 81 | 40 | |
| 60° | P0.7H144S | 0.7 | 144 | 71 | |
| | P0.2H22S | 0.2 | 22 | 11 | |
| | P0.127H47S | 0.127 | 47 | 21 | |
| 85° | P0.2H73S | 0.2 | 73 | 36 | |
| | P0.508H194S | 0.508 | 194 | 99 | |
| 85° | P0.2H75S | 0.2 | 75 | 34 | |
| | | | | | |
| | | | | | |
| | | | | | |

| 角度 | 呼び (溝仕様) | 歯直角ピッチ (P mm) | 参考深度 (H μm) | 参考セル容積 (cm ³ /m ²) |
|----|-------------|------------------|----------------|--|
| 0° | P0.1H7S | 0.1 | 7 | 4 |
| | P0.1H11K | 0.1 | 11 | 6 |
| | P0.2H8K | 0.2 | 8 | 6 |
| | P0.1H11K | 0.1 | 11 | 7 |
| | P0.125H12K | 0.125 | 12 | 8 |
| | P0.125H14K | 0.125 | 14 | 8 |
| | P0.1H15K | 0.1 | 15 | 8 |
| | P0.1H18S | 0.1 | 18 | 9 |
| | P0.125H19K | 0.125 | 19 | 11 |
| | P0.15H21S | 0.15 | 21 | 13 |
| | P0.2H18K | 0.2 | 18 | 13 |
| | P0.2H20K | 0.2 | 20 | 13 |
| | P0.2H22K | 0.2 | 22 | 15 |
| | P0.2H29K | 0.2 | 29 | 18 |
| | P0.2H32K | 0.2 | 32 | 18 |
| | P0.2H34K | 0.2 | 34 | 19 |
| | P0.2H43K | 0.2 | 43 | 22 |
| | P0.2H42K | 0.2 | 42 | 23 |
| | P0.3H39K | 0.3 | 39 | 25 |
| | P0.3H41K | 0.3 | 41 | 26 |
| | P0.3H47K | 0.3 | 47 | 28 |
| | P0.3H47K | 0.3 | 47 | 30 |
| | P0.3H44K | 0.3 | 44 | 30 |
| | P0.3H54K | 0.3 | 54 | 33 |
| | P0.4H50K | 0.4 | 50 | 37 |
| | P0.4H66K | 0.4 | 66 | 48 |
| | P0.4H91K | 0.4 | 91 | 58 |
| | P0.4H127K | 0.4 | 127 | 68 |
| | P0.45H133K | 0.45 | 133 | 77 |
| | P0.45H136K | 0.45 | 136 | 91 |
| | P0.45H139K | 0.45 | 139 | 91 |
| | P0.6H163K | 0.6 | 163 | 103 |
| | | | | |
| | | | | |
| | | | | |

・塗布条件、塗布液の物性により膜厚の差異が発生する場合がございます。
 ・一覧表に掲載していない仕様もございます。ご要望する仕様がない場合はお問い合わせ下さい。
 ・参考深度及び参考セル容積は変更となる可能性がございます。
 ・※の仕様についてはサイズ(径、長さ)によって製作出来ない可能性がございますのでご相談下さい。